



PERRY JOHNSON LABORATORY ACCREDITATION, INC.

Certificate of Accreditation

Perry Johnson Laboratory Accreditation, Inc. has assessed the Laboratory of:

Herb Curry, Inc.

1701 Leonard Road, Mt. Vernon, IN 47620

(Hereinafter called the Organization) and hereby declares that Organization is accredited in accordance with the recognized International Standard:

ISO/IEC 17025:2005

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (as outlined by the joint ISO-ILAC-IAF Communiqué dated January 2009):

Flammability, Toxicity, Heat Release, and Smoke Density Testing *(As detailed in the supplement)*

Accreditation claims for such testing and/or calibration services shall only be made from addresses referenced within this certificate. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.

For PJLA:

Tracy Szerszen
President/Operations Manager

Initial Accreditation Date:

July 4, 2014

Issue Date:

July 14, 2016

Expiration Date:

October 31, 2018

Accreditation No.:

80445

Certificate No.:

L16-294

Perry Johnson Laboratory
Accreditation, Inc. (PJLA)
755 W. Big Beaver, Suite 1325
Troy, Michigan 48084

The validity of this certificate is maintained through ongoing assessments based on a continuous accreditation cycle. The validity of this certificate should be confirmed through the PJLA website: www.pjllabs.com



Certificate of Accreditation: Supplement

Herb Curry, Inc.

1701 Leonard Road, Mt. Vernon, IN 47620
 Contact Name: Kent Wenderoth Phone: 812-838-6703

Accreditation is granted to the facility to perform the following testing:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Thermodynamic ^F	Aerospace Interior Materials	Flammability	FAA Standard FAR 25 Appendix F	As required by the Test Method
			Part I (b) 4	60 Second Vertical Bunsen Burner
			Part I (b) 4	12 Second Vertical Bunsen Burner
			Part I (b) 5	Horizontal Bunsen Burner
			Part I (b) 6	45-Degree Bunsen Burner
			Airbus Standard ABD 0031	As required by the Test Method
			AITM2-0002A	60 Second Vertical Bunsen Burner
			AITM2-0002B	12 Second Vertical Bunsen Burner
			AITM2-0003	Horizontal Bunsen Burner
			AITM2-0004	45-Degree Bunsen Burner
			Boeing	As required by the Test Method
			BSS 7230: F1	60 Second Vertical Bunsen Burner
			BSS 7230: F2	12 Second Vertical Bunsen Burner
			BSS 7230: F3	Horizontal Bunsen Burner (Maximum burn rate 2.5")
			BSS 7230: F4	Horizontal Bunsen Burner (Maximum burn rate 4.0")
			BSS 7230: F5	45-Degree Bunsen Burner
			Toxicity	Airbus Standard ABD 0031
		AITM3-0005		(ppm) Flaming mode (ppm) Non-Flaming mode
		Boeing		As required by the Test Method
		BSS 7239		(ppm) Flaming mode (ppm) Non-Flaming mode
		Heat Release Test	FAA Standard FAR 25 Appendix F	As required by the Test Method
			Part IV	Rate of Heat Release (OSU)



Certificate of Accreditation: Supplement

Herb Curry, Inc.

1701 Leonard Road, Mt. Vernon, IN 47620
Contact Name: Kent Wenderoth Phone: 812-838-6703

Accreditation is granted to the facility to perform the following testing:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Thermodynamic ^F	Aerospace Interior Materials	Heat Release Test	Airbus Standard ABD 0031	As required by the Test Method
			AITM2-0006	Rate of Heat Release (OSU)
			Boeing	As required by the Test Method
			BSS 7322	Rate of Heat Release (OSU)
		Smoke Density	FAA Standard FAR 25 Appendix F	As required by the Test Method
			Part V	(Dm) Flaming mode only
			Airbus Standard ABD 0031	As required by the Test Method
			AITM2-0007A	(Dm) Flaming mode only
			AITM2-0007B	(Dm) Flaming mode (Dm) Non-Flaming mode
			Boeing	As required by the Test Method
BSS 7238	(Dm) Flaming mode (Dm) Non-Flaming mode			

- The presence of a superscript F means that the laboratory performs testing of the indicated parameter at its fixed location. Example: Outside Micrometer^F would mean that the laboratory performs this testing at its fixed location.