# PERRY JOHNSON LABORATORY ACCREDITATION, INC.

# *Certificate of Accreditation*

*Perry Johnson Laboratory Accreditation, Inc. has assessed the Laboratory of:*

## ***Herb Curry, Inc.***

***1701 Leonard Road, Mt Vernon, IN 47620***

*(Hereinafter called the Organization) and hereby declares that Organization is accredited in accordance with the recognized International Standard:*

## ISO/IEC 17025:2017

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system
(as outlined by the joint ISO-ILAC-IAF Communiqué dated April 2017):

***Thermodynamic Testing***
***(As detailed in the supplement)***

Accreditation claims for such testing and/or calibration services shall only be made from addresses referenced within this certificate. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.

For PJLA:

Tracy Szerszen
President

Perry Johnson Laboratory Accreditation, Inc. (PJLA)
755 W. Big Beaver, Suite 1325
Troy, Michigan 48084

| *Initial Accreditation Date:* | *Issue Date:* | *Expiration Date:* |
|---|---|---|
| July 04, 2014 | July 09, 2024 | October 31, 2026 |

| *Accreditation No.:* | *Certificate No.:* |
|---|---|
| 80445 | L24-514 |

*The validity of this certificate is maintained through ongoing assessments based on a continuous accreditation cycle. The validity of this certificate should be confirmed through the PJLA website: www.pjlabs.com*

# *Certificate of Accreditation: Supplement*

**Herb Curry, Inc.**
1701 Leonard Road, Mt Vernon, IN 47620
Contact Name: Mr. Kent Wenderoth Phone: 812-838-6703

*Accreditation is granted to the facility to perform the following testing:*

| FLEX CODE | FIELD OF TEST | ITEMS, MATERIALS, OR PRODUCTS TESTED | COMPONENT, CHARACTERISTIC, PARAMETER TESTED | SPECIFICATION OR STANDARD METHOD | TECHNOLOGY OR TECHNIQUE USED |
|---|---|---|---|---|---|
| | Thermodynamic [F] | Aerospace Interior Materials | Flammability | FAA Standard, FAR 25 Appendix F | |
| F1, F2, F5 | | | | Part I (b) 4 | 60 Second Vertical Bunsen Burner |
| F1, F2, F5 | | | | Part I (b) 4 | 12 Second Vertical Bunsen Burner |
| F1, F2, F5 | | | | Part I (b) 5 | Horizontal Bunsen Burner |
| F1, F2, F5 | | | | Part I (b) 6 | 45-Degree Bunsen Burner |
| | | | | Airbus Standard, ABD 0031 | |
| F1, F2, F5 | | | | AITM2-0002A | 60 Second Vertical Bunsen Burner |
| F1, F2, F5 | | | | AITM2-0002B | 12 Second Vertical Bunsen Burner |
| F1, F2, F5 | | | | AITM2-0003 | Horizontal Bunsen Burner |
| F1, F2, F5 | | | | AITM2-0004 | 45-Degree Bunsen Burner |
| | | | | Boeing Specification Support Standard | |
| F1, F2, F5 | | | | BSS 7230 F1 | 60 Second Vertical Bunsen Burner |
| F1, F2, F5 | | | | BSS 7230 F2 | 12 Second Vertical Bunsen Burner |
| F1, F2, F5 | | | | BSS 7230 F3 | Horizontal Bunsen Burner 2.5" |
| F1, F2, F5 | | | | BSS 7230 F4 | Horizontal Bunsen Burner 4.0" |
| F1, F2, F5 | | | | BSS 7230 F5 | 45-Degree Bunsen Burner |
| | | | Toxicity | Airbus Standard, ABD 0031 | |
| F1, F2, F5 | | | | AITM3-0005 | Combustion Analyzer Draeger Tubes |
| | | | | Boeing Specification Support Standard | |
| F1, F2, F5 | | | | BSS 7239 | Combustion Analyzer Draeger Tubes |
| | | | Heat Release | FAA Standard, FAR 25 Appendix F | |
| F1, F2, F5 | | | | Part IV | OSU Heat Release Machine |
| | | | | Airbus Standard, ABD 0031 | |
| F1, F2, F5 | | | | AITM2-0006 | OSU Heat Release Machine |
| | | | | Boeing Specification Support Standard | |
| F1, F2, F5 | | | | BSS 7322 | OSU Heat Release Machine |

# *Certificate of Accreditation: Supplement*

**Herb Curry, Inc.**
1701 Leonard Road, Mt Vernon, IN 47620
Contact Name: Mr. Kent Wenderoth Phone: 812-838-6703

*Accreditation is granted to the facility to perform the following testing:*

| FLEX CODE | FIELD OF TEST | ITEMS, MATERIALS, OR PRODUCTS TESTED | COMPONENT, CHARACTERISTIC, PARAMETER TESTED | SPECIFICATION OR STANDARD METHOD | TECHNOLOGY OR TECHNIQUE USED |
|---|---|---|---|---|---|
| | Thermodynamic [F] | Aerospace Interior Materials | Smoke Density | FAA Standard, FAR 25 Appendix F | |
| F1, F2, F5 | | | | Part V | Smoke Density Chamber |
| | | | | Airbus Standard, ABD 0031 | |
| F1, F2, F5 | | | | AITM2-0007A | Smoke Density Chamber |
| F1, F2, F5 | | | | AITM2-0007B | Smoke Density Chamber |
| | | | | Boeing Specification Support Standard | |
| F1, F2, F5 | | | | BSS 7238 | Smoke Density Chamber |

1. The presence of a superscript F means that the laboratory performs testing of the indicated parameter at its fixed location.

2. Flex Code:
   F1-Introduction of the testing of a new item, material, matrix, or product for an accredited test method
   F2-Introduction of a new version of an accredited standard method (with no modifications)
   F3-Introduction of a new parameter/component/analyte to an accredited test method
   F4-Introduction of a new version or modifications of an accredited non-standard method
   F5-Introduction of a new method that is equivalent to an accredited method (using same technology or technique)