# PERRY JOHNSON LABORATORY ACCREDITATION, INC.

# *Certificate of Accreditation*

*Perry Johnson Laboratory Accreditation, Inc. has assessed the Organization of:*

## ***Herb Curry, Inc.***

***1701 Leonard Road, Mt Vernon, IN 47620***

*and hereby declares that the Organization is accredited in accordance with the recognized International Standard:*

## ISO/IEC 17025:2017

Whereby, technical competence has been confirmed for the associated scope supplement, in the fields of:

## ***Thermodynamic Testing***

***(As detailed in the supplement)***

Accreditation claims for conformity assessment activities shall only be made from the addresses referenced within this certificate and shall apply solely to those activities identified in the related scope. This Accreditation is granted subject to the Accreditation Body rules governing the Accreditation referred to above, and the Organization hereby commits to observing and complying with those rules in their entirety.

For PJLA:

Tracy Szerszen
President

Perry Johnson Laboratory
Accreditation, Inc. (PJLA)
755 W. Big Beaver, Suite 1325
Troy, Michigan 48084

| *Initial Accreditation Date:* | *Issue Date:* | *Expiration Date:* |
|---|---|---|
| July 04, 2014 | September 01, 2026 | October 31, 2028 |

| *Accreditation No.:* | *Certificate No.:* |
|---|---|
| 80445 | L26-797 |

*The validity of this certificate is maintained through ongoing assessments based on a continuous accreditation cycle. The validity of this certificate should be confirmed through the PJLA website: www.pjlabs.com*

# *Certificate of Accreditation: Supplement*


**Herb Curry, Inc.**
1701 Leonard Road, Mt Vernon, IN 47620
Contact Name: Kent Wenderoth Phone: 812-838-6703


*Accreditation is granted to the facility to perform the following conformity assessment activities:*

| FIELD OF TEST | ITEMS, MATERIALS, OR PRODUCTS TESTED | COMPONENT, CHARACTERISTIC, PARAMETER TESTED | SPECIFICATION OR STANDARD METHOD | TECHNOLOGY OR TECHNIQUE USED | FLEX CODE | LOCATION OF ACTIVITY |
|---|---|---|---|---|---|---|
| Thermodynamic | Aerospace Interior Materials | Flammability | FAA Standard, FAR 25 Appendix F Part I (b) 4 | 60 Second Vertical Bunsen Burner | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Flammability | FAA Standard, FAR 25 Appendix F Part I (b) 4 | 12 Second Vertical Bunsen Burner | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Flammability | FAA Standard, FAR 25 Appendix F Part I (b) 5 | Horizontal Bunsen Burner | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Flammability | FAA Standard, FAR 25 Appendix F Part I (b) 6 | 45-Degree Bunsen Burner | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Flammability | Airbus Standard, ABD 0031 AITM2-0002A | 60 Second Vertical Bunsen Burner | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Flammability | Airbus Standard, ABD 0031 AITM2-0002B | 12 Second Vertical Bunsen Burner | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Flammability | Airbus Standard, ABD 0031 AITM2-0003 | Horizontal Bunsen Burner | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Flammability | Airbus Standard, ABD 0031 AITM2-0004 | 45-Degree Bunsen Burner | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Flammability | Boeing Specification Support Standard, BSS 7230 F1 | 60 Second Vertical Bunsen Burner | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Flammability | Boeing Specification Support Standard, BSS 7230 F2 | 12 Second Vertical Bunsen Burner | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Flammability | Boeing Specification Support Standard, BSS 7230 F3 | Horizontal Bunsen Burner 2.5” | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Flammability | Boeing Specification Support Standard, BSS 7230 F4 | Horizontal Bunsen Burner 4.0” | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Flammability | Boeing Specification Support Standard, BSS 7230 F5 | 45-Degree Bunsen Burner | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Toxicity | Airbus Standard, ABD 0031 AITM3-0005 | Combustion Analyzer Draeger Tubes | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Toxicity | Boeing Specification Support Standard, BSS 7239 | Combustion Analyzer Draeger Tubes | F1, F2, F5 | F |

# *Certificate of Accreditation: Supplement*

## Herb Curry, Inc.

1701 Leonard Road, Mt Vernon, IN 47620
Contact Name: Kent Wenderoth Phone: 812-838-6703

*Accreditation is granted to the facility to perform the following conformity assessment activities:*

| FIELD OF TEST | ITEMS, MATERIALS, OR PRODUCTS TESTED | COMPONENT, CHARACTERISTIC, PARAMETER TESTED | SPECIFICATION OR STANDARD METHOD | TECHNOLOGY OR TECHNIQUE USED | FLEX CODE | LOCATION OF ACTIVITY |
|---|---|---|---|---|---|---|
| Thermodynamic | Aerospace Interior Materials | Heat Release | FAA Standard, FAR 25 Appendix F Part IV | OSU Heat Release Machine | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Heat Release | Airbus Standard, ABD 0031 AITM2-0006 | OSU Heat Release Machine | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Heat Release | Boeing Specification Support Standard, BSS 7322 | OSU Heat Release Machine | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Smoke Density | FAA Standard, FAR 25 Appendix F Part V | Smoke Density Chamber | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Smoke Density | Airbus Standard, ABD 0031 AITM2-0007A | Smoke Density Chamber | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Smoke Density | Airbus Standard, ABD 0031 AITM2-0007B | Smoke Density Chamber | F1, F2, F5 | F |
| Thermodynamic | Aerospace Interior Materials | Smoke Density | Boeing Specification Support Standard, BSS 7238 | Smoke Density Chamber | F1, F2, F5 | F |

1. Location of activity:

| Location | Location |
|---|---|
| F | Conformity assessment activity is performed at the CABs fixed facility |

2. Flex Code:
   F0- Fixed scope item. No deviations allowed to the line item as identified, except for updating to the most recent version of an accredited standard method after verification.
   F1- Laboratory has the capability to test a new item, material, matrix, or product similar in composition to item, material, matrix, or product identified on the scope
   F2- Laboratory has the capability to introduce the newest revision of an accredited authoritative standard method (with no modifications) identified on the scope
   F3- Laboratory has the capability to introduce a parameter/component/analyte to an accredited test method identified on the scope
   F4- Laboratory has the capability to introduce a new revision of an accredited non-standard method using the same technology or technique identified on the scope
   F5- Laboratory has the capability to introduce a validated method that is equivalent to an accredited method (using same technology or technique) identified on the scope